



AEROTM
CONCHEM LLP

AN ISO 9001 : 2008 CERTIFIED COMPANY

AQUAPEL WB

Deeply Penetrating Water – Based Silane/siloxane Water Repellent For Vertical Surfaces

Description

AQUAPEL WB is a clear ready-to-use water-based, VOC compliant silane/siloxane water repellent and “chloride screen” for the protection of concrete and masonry. AQUAPEL WB penetrates more deeply than conventional water-or solvent-based water repellents. Low odor and alkaline stable. AQUAPEL WB is ideal for field or in-plant application to concrete and most masonry. It prolongs the clean appearance of buildings, reduces chemical attack and minimizes efflorescence. Due to the excellent waterrepell properties dirt and other atmospheric impurities are washed off by rain and its clean appearance is maintained for a longer period.

Uses

AQUAPEL WB is suitable for external application to exterior walls of brick or concrete blocks, cement renderings, asbestos cement, concrete and all types of stone, including limestone. Also used as an injection damp course fluid and provides a durable barrier to water penetration of porous surfaces.

Advantages

- Formulated for concrete and masonry.
- Penetrates to produce long-lasting protection on vertical surfaces
- Water-based formula minimizes explosion and fire hazards.
- Low odor reduces risk of application to occupied buildings.
- Ready-to-use, non-flammable, non-volatile.
- Invisible, long lasting protection.
- No film. Leaves surface breathable – allows interior moisture to escape
- Alkaline stable.
- Treated surfaces “breathe”- does not trap moisture
- Increases free-flow resistance and minimizes efflorescence.
- Deeply penetrates into substrates.

Instruction for use

Surface Preparation

Areas to be treated shall be clean and dry for penetration. Allow 24 hours after rain before applying. Cure mortar joints of new masonry surfaces for 14 days prior to treatment. Clean off mud, scale, coatings or efflorescence. Repair mortar joints, other than hairline cracks, and allow to cure a minimum of 72 hours before applying AQUAPEL WB.

Typical Properties & Specifications:

Sr.No	Properties	Specification
1	Colour	Clear liquid, dries invisible
2	Drying Time at 30 °C	Three (4) hours
3	Surface Gloss	None
4	Water Repellency	Excellent.
5	VOC, gms/ Litre	< 50

Application

Mix material thoroughly before and during application. Apply by low-pressure, non-atomizing spray or by brush (for small area application). Two coats are recommended. Permeable units require several flood coats NOTE: AQUAPEL WB requires approximately seven (7) days after application to develop its maximum water repellency. After this initial curing period, surfaces remain permanently treated to resist water penetration. Fully cured surfaces also resist further treatment.

Cleaning

Tools should be cleaned immediately after use with clean water.

Packing

AQUAPEL WB is supplied in 1, 5, 10, 50 & 100 litre containers.

Coverage

1 ltr. AQUAPEL WB will cover approx. 4 to 5 m² of surface depends upon the substrates.



AEROTM
CONCHEM LLP

AN ISO 9001 : 2008 CERTIFIED COMPANY

AQUAPEL WB

Deeply Penetrating Water – Based Silane/siloxane Water Repellent For Vertical Surfaces

Shelf Life & Storage

AQUAPEL WB has a shelf life of 12 months from date of manufacture when kept at a temperature between 5 °C to 45 °C and store in the original, unopened bags. All material shall be stored under cover in a manner that will prevent damage preferable on pallets and protected from excessive heat and moisture. Do not freeze.

Quality Assurance

AERO CONCHEM LLP is a firm of Assessed Capability. The company's quality system conforms to ISO 9001:2008.

Health & Safety

AQUAPEL WB should not come into contact with skin, eyes or be swallowed. Protective glasses should be worn during mixing and application. Should SAYOBOND SBR 20 come into contact with skin, remove before hardening by washing with soap and water. Should accidental eye contact occur wash with plenty of water and seek medical advice. If swallowed seek medical advice immediately. Do not induce vomiting. For full health and safety data refer to Product Safety Data Sheet.

OUR RANGE OF PRODUCTS



Reg. Office:

201, Shrinath Square, Shuklanagar Char Rasta,
Nr.Reliance Fresh Store, Mehsananagar Road,
Nizampura - Vadodara - 24.

Phone:

(0265) 6556699, 2886535

Works:

Plot No. 265, Haridham Sokhada Road,
Village - Sokhada, Dist. - Vadodara.
State - Gujarat - INDIA.

E-mail:

sales@aeroconchem.com

Website:

www.aeroconchem.com

JAN/2017/01

for more details visit us : www.aeroconchem.com